SAFETY DATA SHEET

JCB Optimum Performance Gear Oil 75W-140



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: JCB Optimum Performance Gear Oil 75W-140
Viscosity or Type	: SAE 75W-140
Material uses	: Lubricating oil for automotive transmissions

1.2 Relevant identified uses of the substance or mixture and uses advised against Not applicable.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Distributor	JCB Service World Parts Centre Waterloo Park Beamhurst Staffordshire England ST14 5PA	
e-mail address of person responsible for this SDS	aftermarketproduct.hotline@jcb.com (Mon to Fri 9.00am to 4.00pm UK time) Communication in English only)

1.4 Emergency telephone number

Telephone number	: +44 1865 407333 - English language only
	+1 202 464 2554 - English language only specific to US and Canada

SECTION 2: Hazards identification

2.1 Classification of the subs	tance or mixture			
Product definition	: Mixture			
Classification according to	Regulation (EC) No. 1272/2008 [CLP/GHS]			
Not classified.				
The product is not classified a	is hazardous according to Regulation (EC) 1272/2008 as amended.			
Ingredients of unknown toxicity	: None.			
Ingredients of unknown ecotoxicity	: None.			
See Section 11 for more detailed information on health effects and symptoms.				
2.2 Label elements				
Signal word	: No signal word.			
Hazard statements	: No known significant effects or critical hazards.			
Precautionary statements				
Prevention	: Not applicable.			
Response	: Not applicable.			
Storage	: Not applicable.			
Disposal	: Not applicable.			

SECTION 2: Hazards identification

Supplemental label elements	: Contains Polysulfides, di-tert-Bu and Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction. Safety data sheet available on request.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requiren	<u>nents</u>
Containers to be fitted with child-resistant fastenings	: Not applicable.
Tactile warning of danger	: Not applicable.

2.3 Other hazards

Other hazards which do : Prolonged or repeated contact may dry skin and cause irritation. **not result in classification**

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре	Notes
Polysulfides, di-tert-Bu	REACH #: 01-2119540515-43 EC: 273-103-3 CAS: 68937-96-2	≤4.6	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	[1]	-
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8	≤5	Asp. Tox. 1, H304	[1] [2]	H-L
Mineral oil Reaction products of bis (4-methylpentan-2-yl) dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	CAS: * REACH #: 01-2119493620-38 EC: 931-384-6	≤3 ≤2	Asp. Tox. 1, H304 Acute Tox. 4, H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1] [1]	-
			See Section 16 for the full text of the H statements declared above.		

* CAS: 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0

The mineral oils in the product contain < 3% DMSO extract (IP 346).

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

M Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

JCB Optimum Performance Gear Oil 75W-140

SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	 Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	: Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising f	rom	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Date of issue/Date of revision		:15-06-2018 Date of previous issue :20-05-2017 Version :1.02 3/13

Date of issue/Date of revision	:15-06-2018	Date of previous issue	:20-05-2017	Version : 1.02	3/13
--------------------------------	-------------	------------------------	-------------	----------------	------

JCB Optimum Performance Gear Oil 75W-140

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.
5010110115	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Distillates (petroleum), hydrotreated light paraffinic	EU OEL (Europe). TWA: 5 mg/m ³ 8 hours. STEL: 10 mg/m ³ 15 minutes.
procedures atmosphere of of the ventilat protective equ the following: the assessme limit values at atmospheres of exposure to (Workplace a for the measu	contains ingredients with exposure limits, personal, workplace or biological monitoring may be required to determine the effectiveness ion or other control measures and/or the necessity to use respiratory aipment. Reference should be made to monitoring standards, such as European Standard EN 689 (Workplace atmospheres - Guidance for ent of exposure by inhalation to chemical agents for comparison with and measurement strategy) European Standard EN 14042 (Workplace - Guide for the application and use of procedures for the assessment o chemical and biological agents) European Standard EN 482 tmospheres - General requirements for the performance of procedures arement of chemical agents) Reference to national guidance r methods for the determination of hazardous substances will also be

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

JCB Optimum Performance Gear Oil 75W-140

SECTION 8: Exposure controls/personal protection

Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physica	and chemical properties
Appearance	
Physical state	: Liquid. [Oily liquid.]
Appearance	: Clear.
Colour	: Yellow [Light]
Odour	: Characteristic.
Odour threshold	: Not available.
рН	: 7
Melting point/freezing point	: <-42°C
Initial boiling point and boiling range	: >300°C
Flash point	: Open cup: >170°C [ASTM D92.]
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not applicable.
Upper/lower flammability or explosive limits	: Not available.
Vapour pressure	: <0.1 kPa [room temperature]
Vapour density	: Not available.
Relative density	: 0.874
Solubility(ies)	: Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: >300°C
Decomposition temperature	: >300°C
Viscosity (40°C)	: 186 cSt
Viscosity (100°C)	: 24.9 cSt
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.

9.2 Other information

SECTION 10: Stability and reactivity					
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
10.2 Chemical stability	: The product is stable.				
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
10.4 Conditions to avoid	: No specific data.				
Date of issue/Date of revision	:15-06-2018 Date of previous issue :20-05-2017 Version :1.02 6/13				

JCB Optimum Performance Gear Oil 75W-140

SECTION 10: Stability and reactivity

10.5 Incompatible materials	: Reactive or incompatible with the following materials:
	Strong oxidising materials

10.6 Hazardous: Under normal conditions of storage and use, hazardous decomposition productsdecomposition productsshould not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Result	Species	Dose	Exposure
LC50 Inhalation Dusts and mists	Rat	3900 mg/m ³	4 hours
LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
LC50 Inhalation Dusts and mists	Rat - Male, Female	5.53 mg/l	4 hours
LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg >5000 mg/kg	-
	LC50 Inhalation Dusts and mists LD50 Dermal LD50 Oral LC50 Inhalation Dusts and mists LD50 Dermal	LC50 Inhalation Dusts and mistsRatLD50 DermalRabbit - Male, FemaleLD50 OralRat - Male, FemaleLC50 Inhalation Dusts and mistsRat - Male, FemaleLD50 DermalRat - Male, FemaleLC50 Inhalation Dusts and mistsRat - Male, FemaleLD50 DermalRat - Male, Female	LC50 Inhalation Dusts and mists LD50 DermalRat3900 mg/m³LD50 DermalRabbit - Male, Female Rat - Male, Female>5000 mg/kgLC50 Inhalation Dusts and mists LD50 DermalRat - Male, Female Rat - Male,

Acute toxicity estimates

Route	ATE value	
Oral	25125.6 mg/kg	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Sistillates (petroleum), hydrotreated light paraffinic	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
	Skin - Oedema	Rabbit	0	72 hours	7 days
	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
Mineral oil	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
	Skin - Oedema	Rabbit	0	72 hours	7 days
	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours

Conclusion/Summary : Not available.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
♥istillates (petroleum), hydrotreated light paraffinic	skin	Guinea pig	Not sensitizing
Mineral oil	skin	Guinea pig	Not sensitizing
0	. N		

Conclusion/Summary

: Not available.

Mutagenicity

SECTION 11: Toxicological information

Product/ingredient name	Test	Experiment	Result
Distillates (petroleum), hydrotreated light paraffinic	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
Mineral oil	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

Conclusion/Summary

: Not available.

: Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Sistillates (petroleum), hydrotreated light paraffinic	Negative - Dermal - TC	Mouse - Female	-	78 weeks
Mineral oil	Negative - Dermal - TC	Mouse - Female	-	78 weeks
Conclusion/Summary	: Not available.			

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Distillates (petroleum), hydrotreated light paraffinic	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-
Mineral oil	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-

Conclusion/Summary

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Sistillates (petroleum), hydrotreated light paraffinic	Negative - Dermal	Rat	2000 mg/kg	7 days per week
Mineral oil	Negative - Dermal	Rat	2000 mg/kg	7 days per week

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1
Mineral oil	ASPIRATION HAZARD - Category 1

Information on likely routes : Not available. of exposure

Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
-------------	---------------------

SECTION 11: Toxicological information

Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects Long term exposure	: Not available.
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure		
Distillates (petroleum), hydrotreated light paraffinic	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week		
	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day		
	Sub-acute NOAEL Inhalation Dusts and mists	Rat - Male	>980 mg/m³	4 weeks; 5 days per week		
Mineral oil	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week		
	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day		
	Sub-acute NOAEL Inhalation Vapour	Rat - Male	>980 mg/m³	4 weeks; 5 days per week		
Conclusion/Summary	: Not available.					
General	: Prolonged or repeated conta or dermatitis.	act can defat the	skin and lead to irri	tation, cracking and/		
Carcinogenicity	: No known significant effects	or critical hazard	ds.			
Mutagenicity	: No known significant effects	or critical hazard	ds.			
Teratogenicity	: No known significant effects	: No known significant effects or critical hazards.				
Developmental effects	: No known significant effects	or critical hazard	ds.			

Other information

Fertility effects

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Mineral oil	Acute NEL >100 mg/l Fresh water	Algae	72 hours
	Acute NEL >10000 mg/l Fresh water	Daphnia - Daphnia Magma	48 hours
	Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days

: No known significant effects or critical hazards.

Conclusion/Summary : Not available.

. Not availat

12.2 Persistence and degradability

Conclusion/Summary : Not available.

JCB Optimum Performance Gear Oil 75W-140

SECTION 12: Ecological information

0			
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Sistillates (petroleum), hydrotreated light paraffinic	-	-	Inherent
Mineral oil	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
✓olysulfides, di-tert-Bu Distillates (petroleum), hydrotreated light paraffinic	5.6 >3	-	high Iow

12.4 Mobility in soil	
Soil/water partition coefficient (K _{oc})	: Not available.
Mobility	: Not available.

12.5 Results of PBT	and vPvB assessment
PBT	: Not applicable.
vPvB	: Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European waste catalogue (EWC)

Waste code	Waste designation	
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils	
Packaging		
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. 	
Special precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

JCB Optimum Performance Gear Oil 75W-140

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Industrial emissions : Listed (integrated pollution prevention and control) -Air

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

: 1 Hazard class for water (WGK)

Date of issue/Date of revision

JCB Optimum Performance Gear Oil 75W-140

SECTION 15: Regulatory information				
VOC content		Exempt.		
International regulations		Exempt.		
	-	List Schedules I, II & III Chemicals		
Not listed.				
Montreal Protocol (Anne Not listed.	<u>ixes A</u>	<u>, D, C, E</u>)		
Stockholm Convention of Not listed.	on Per	<u>sistent Organic Pollutants</u>		
Rotterdam Convention of Not listed.	on Pric	or Informed Consent (PIC)		
UNECE Aarhus Protocol Not listed.	on PC	<u>DPs and Heavy Metals</u>		
Inventory list				
Australia	:	All components are listed or exempted.		
Canada		At least one component is not listed in DSL but all such components are listed in NDSL.		
China	:	All components are listed or exempted.		
Europe	:	All components are listed or exempted.		
Japan	:	Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined.		
Malaysia	:	Not determined.		
New Zealand	:	Not determined.		
Philippines	:	All components are listed or exempted.		
Republic of Korea	:	All components are listed or exempted.		
Taiwan	:	Not determined.		
Thailand	:	Not determined.		
Turkey	:	Not determined.		
United States	:	All components are listed or exempted.		
Viet Nam	:	Not determined.		
15.2 Chemical safety assessment	:	This product contains substances for which Chemical Safety Assessments are still required.		
SECTION 16: Othe	er inf	ormation		
Indicates information th	at has	changed from previously issued version.		

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Not classified.		

Full text of abbreviated H statements

Date of issue/Date of revision

SECTION 16: Other information			
H302 H304 H317 H318 H411 H412	Harmful if swallowed. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.		
Full text of classifications [CLP/GHS	<u>S]</u>		
Acute Tox. 4, H302 Aquatic Chronic 2, H411 Aquatic Chronic 3, H412 Asp. Tox. 1, H304 Eye Dam. 1, H318	ACUTE TOXICITY (oral) - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1		

SKIN SENSITISATION - Category 1

Skin Sens. 1B, H317	SKIN SENSITISATION - Category 1B
Training advice	: Ensure operatives are trained to minimise exposures.
Date of printing	: 15-06-2018
Date of issue/ Date of revision	: 15-06-2018
Date of previous issue	: 20-05-2017
Version	: 1.02
· · · · · ·	

Notice to reader

Eye Dam. 1, H318 Skin Sens. 1, H317

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.